

Intelligent battery charger and maintainer with electronic control of the charging current, automatic interruption and restart (PULSE-TRONIC). Automatic charge of all maintenance free, sealed batteries (GEL/AGM/START-STOP), and free electrolyte batteries (WET) with 12V voltages of motorcycles, cars, vans, tractors and boats. Characteristics: 3 charge current levels \* warning led for charging status, end of charge, thermostatic interruption due to short circuit of output cables or polarity reversal. Supplied with three different charging cables.



**Pulse Tronic**



**AUTOMOTIVE**

**CONSUMER**




**AUTOMATIC CONTROL OF THE CHARGE LEVEL**

**Pulse Tronic**

**CHARGING STATUS WARNING LED**



**WIDE RANGE OF USE**



**SHORT-CIRCUIT, POLARITY REVERSAL PROTEC.**



**3 DIFFERENT TYPES OF CHARGING CABLES**



Norms: LVD: EN 60335-2-29 EMC: EN 55014-1,2; EMC: EN 61000-3-2,3

CODE	V <sub>ph</sub> V50/60Hz	P W	+ - V	A <sub>EFF</sub> A	A <sub>EN</sub> A	C MIN/MAX Ah15h		W L H cm(L,W,H)	kg
807560	230 1 ph	55	12	4	4	2 70	3	17 6,5 3,5	0,6
BAR CODE									
8004897712 48 2	432								