



T-CHARGE 26 BOOST 12V



Overview

T-CHARGE 26 BOOST 12V

cod. 807562

Intelligent battery charger and maintainer with electronic control of the charging current, and automatic interruption and restart (PULSE-TRONIC).

Normal charge (CHARGE), automatic charge (PULSE-TRONIC) and rapid charge (BOOST), of all maintenance free, sealed batteries (GEL/AGM/START-STOP), and free electrolyte batteries (WET) with 12V voltage of motorcycles, cars, vans, tractors and boats. The CHARGE mode is advisable when the type of battery to be charged is unknown, the PULSE-TRONIC (GEL/AGM or WET) mode allows the automatic control of the battery status.

Features:

- 3 charge current levels
 - warning led for charging status, end of charge, thermostatic interruption due to short circuit of output cables or polarity reversal
- Supplied with three different charging cables.



1 PH 230V



TRACTOR



VAN



MOTORCYCLE



TRUCK



CE MARKING



CAR



EXCAVATOR



EAC CERTIFICATION



BOAT

Technical data



T-CHARGE 26 BOOST 12V

CODE	CODE 807562	A_{EFF}	EFFECTIVE CHARGING CURRENT 16 A		DIMENSIONS 30 - 9,5 - 5,5 cm
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	A_{EN}	RATED CHARGE CURR. EN60335-2-29 16 A	kg	WEIGHT 1,4 kg
F	MAINS FREQUENCY 50 - 60 Hz	C_{MIN}	MIN. RATED REFERENCE CAPACITY 10 Ah	BAR CODE	EAN CODE 800489773861 1
P	CHARGING ABSORBED POWER 220 W	C_{MAX}	MAX RATED REFERENCE CAPACITY 250 Ah		PIECES/PALLET 180 pz/pallet
	CHARGING VOLTAGE 12 V		ADJUSTMENT POSITIONS 3		